

PRODUCT DESCRIPTION	Multi-tone, circular geometric, pattern
NUMBER OF COLORS	5
ABRASION	102,000 Double Rubs
BRAND	Crypton
BREAKING	ASTM D5034-95 (2001) Grab Test - Fill 335 x Warp 241 lbs
CAUTIONS	Do not use strong solvent cleaners.
CLEANING CODE	W - Clean fabrics with water-based cleaning agents or water based foam
CLEANERS APPROVED	Virox 5, Crypton Upholstery Cleaners
CLEANER DISCLAIMER	Dilution ratios must be followed. Materials must be wiped with clean water after use and wiped dry with a clean cloth.
COLLECTION	Crypton Trailblazer
CONSTRUCTION	Crypton, Jacquards, Woven
CONTENT	100% Polyester
CONTENT BACKING	Crypton Green
CROCKING	AATCC 8: Dry = Class 5, AATCC 8: Wet = Class 4.5
ECOFRIENDLY	Crypton Green - Greenguard Gold Certified
ELONGATION	Passes ASTM D5034-09 - Fill 1.44% x Warp 1.53%
FEATURES	Bacteria/Fungal Resistant, Stain Resistant

FINISH	Crypton Green - Permanent moisture, soil resistance and anti-microbial protection
FIRE RETARDANCY	California Technical Bulletin 117 Section E- 2013, UFAC Class 1
INDUSTRY	Contract, Education, Healthcare, Hospitality, Office, Residential
MILDEW RESISTANCE	Mildew Resistant
PILLING	Passes ASTM D3511 - Class 4
RAILROADED	Railroaded
REPEAT LENGTH	7.8" (19.8 cm) Up the Roll
REPEAT WIDTH	15.0" (38.1 cm) Across the Roll
ROLL SIZE	60 yards (55 m)
SEAM SLIPPAGE	Passes ASTM D4034 - Fill 115 x Warp 99 LBF
STYLE	Circles, Contemporary
TEAR STRENGTH	Passes ASTM D2261 - Fill 60 x Warp 23 lbs
TENSILE STRENGTH	Passes ASTM D5034 - Fill 335 x Warp 241 lbs
UV RESISTANCE	Colorfastness to Light AATCC 16 - Grade 4 (40 Hours)
USES	Decorative Accessories, Healthcare Seating, Hospitality Seating, Office Seating, Residential Seating
WEIGHT	362.02 Grams per Square Meter, 16.38 Ounces per Linear Yard, 10.68 Ounces per Square Yard
WIDTH	55" (140 cm)

