

<b>NUMBER OF COLORS</b>	7
<b>ABRASION</b>	100,000 Double Rubs
<b>BRAND</b>	Crypton
<b>CAUTIONS</b>	Do not use strong solvent cleaners.
<b>CLEANING CODE</b>	W - Clean fabrics with water-based cleaning agents or water based foam
<b>CLEANING INSTRUCTIONS</b>	If bleach cleaning is required: Spray a 90% water/10% bleach mixture on the fabric. Thoroughly rinse with clean water after bleach-cleaning to remove any residual bleach and pat dry.
<b>CLEANERS APPROVED</b>	Virox 5, Crypton Upholstery Cleaners
<b>CLEANER DISCLAIMER</b>	Dilution ratios must be followed. Materials must be wiped with clean water after use and wiped dry with a clean cloth.
<b>COLLECTION</b>	Crypton Innovation Stack Book
<b>CONSTRUCTION</b>	Crypton, Jacquards, Woven
<b>CONTENT</b>	100% Polyester
<b>CONTENT BACKING</b>	Crypton
<b>CROCKING</b>	AATCC 8: Dry = Class 5, AATCC 8: Wet = Class 4.5
<b>FEATURES</b>	Bacteria/Fungal Resistant, Stain Resistant
<b>FINISH</b>	Crypton - Permanent moisture, soil resistance and anti-microbial protection
<b>FIRE RETARDANCY</b>	CALTB117-2013, UFAC Class 1

<b>INDUSTRY</b>	Contract, Education, Healthcare, Hospitality, Office, Residential
<b>MILDEW RESISTANCE</b>	Mildew Resistant
<b>PILLING</b>	Passes ASTM D3511 - Class 5
<b>RAILROADED</b>	Non Railroaded
<b>REPEAT LENGTH</b>	13.9" (35.2 cm) Up the Roll
<b>REPEAT WIDTH</b>	14.6" (37.2 cm) Across the Roll
<b>ROLL SIZE</b>	55 yards (50 m)
<b>SEAM SLIPPAGE</b>	Passes ASTM D4034 - Fill 93 x Warp 92 LBF
<b>STYLE</b>	Contemporary
<b>TEAR STRENGTH</b>	Passes ASTM D2261 - Fill 61 x Warp 25 lbs
<b>TENSILE STRENGTH</b>	Passes ASTM D5034 - Fill 399 x Warp 310 lbs
<b>UV RESISTANCE</b>	Colorfastness to Light AATCC 16 - Grade 4 (40 Hours)
<b>USES</b>	Decorative Accessories, Healthcare Seating, Hospitality Seating, Office Seating, Residential Seating
<b>WEIGHT</b>	427.97 Grams per Square Meter, 12.62 Ounces per Square Yard, 19.63 Ounces per Linear Yard
<b>WIDTH</b>	56" (142 cm)



